

## Quick & Easy Floor Installation Guide

*Please remove tiles from boxes for 24 hours prior to installation*

### Tools

- 1. Carpet Knife, Tape Measure, Chalk, Straight Edge**
- 2. Adhesive or Double-sided tape**

### Step 1

Measure the size of the room – (length \* width) to determine the size of the room. If the room is not a perfect square, then divide the room into smaller rectangles to obtain total area of the room. Each box has 20 tiles equivalent to 5 square meters. Remove old carpet and clear the working area of all furniture. The floor must be dry, clean, level and free from debris. Cracks and holes must be filled for maximum performance.

### Step 2

Divide the room into 4 equal parts using the chalk and straight edge. Apply the adhesive or the gridlines using double sided tape. Directional arrows are printed on the back of each tile. Since this is plain carpet, the broadloom effect can be achieved by laying the tile in the same direction. Different colors can also be placed together to achieve a checkered pattern.

### Step 3

Tiles overlapping with the side walls can be cut using a carpet knife. Using a straight edge and chalk as a guide, slowly cut the borders. It is advisable to cut the tile from the back to get a clean finish. For a clean finish, place a new tile backwards on top of the overlapping tile and draw a reference line to cut the tile.

### Precautions:

When moving heavy furniture, use runners to avoid shifting. Maximum working temperature is 50 degrees Celsius.

### Replacement and Maintenance:

Heavily damaged tiles can be replaced from old stock or buying new from the store. Any visual remarks from the new tile will disappear over a short time. Use vacuum cleaners to prevent the effects of soiling. In case of stains, use the regular stain removers.